

GLT6-A light tower

Innovation comes through a careful management of space. The *GLT Series* combines all market requirements inside a very compact frame. **GLT6-A** is the version with 6 LED floodlights and a hydraulic lifting system.

FEATURES & BENEFITS:

LED lamps

6x320W high-efficiency LED floodlights with a high lumen output and a long life expectation of 50,000 working hours!

Large “seagull-wing” doors for the best accessibility

Two large compass-top doors with «seagull-wing» shape provide a complete access to all technical components for a safe, fast and convenient maintenance.

Simplified control panel

The new control panel is easier to use and includes the new DSE L401-MKII advanced digital controller able to manage every function of the light tower. Thanks to a small window on the door, the digital controller is visible even when the door is closed. The control panel is completed with two 16A outlet sockets, a 16A inlet plug, circuit breakers, fuses, a fuel level gauge, a grounding pin and an emergency stop button.

Darkness sensor and timer

A timer is installed as standard. A darkness sensor can be requested as an option.

Low environmental impact

Thanks to the low power absorption of the high-efficiency LEDs, the GLT6-A can run with a small engine (3 cylinders). This allows to drastically reduce the fuel consumption and the carbon emissions of the unit.

Large fuel tank with a liquid containment tank

Every GLT model is equipped with a fuel tank made of plastic, deleting any possible trouble with rust and reducing the total weight of the unit. A liquid containment tank is installed as standard to avoid any risk of leakages on the ground. The large capacity of the fuel tank guarantees a long running time and reduces refueling costs: an ideal solution for use in remote areas!

Road trailer with foldable drawbar

GLT6-A is equipped as standard with a road trailer with a long, foldable drawbar which allows optimized dimensions for storage and transport.

Compact shape

GLT are designed to be loaded in high quantity on a 13.6m truck or on a 40" HC container, a perfect solution to save transport costs! Moreover, the standard tie-down points assure more safety during transport.



Picture shown may not reflect actual configuration.

GLT6-A K3	Technical Data
Minimum dimensions (L x W x H)	2156 x 1400 x 2403 mm
Maximum dimensions (L x W x H)	3095 x 2166 x 8387 mm
Dry weight	1000 kg
Mast lifting system	Hydraulic
Mast rotation	340°
Floodlights	6x 320W LED
Luminous flux	276000 Lm
Illuminated area (1 lux min)	12600 m ²
Engine	Kubota D1105
Engine cooling	Liquid
Cylinders (q.ty)	3
Engine speed (50/60 Hz)	1500 / 1800 rpm
Alternator (50/60 Hz)	8kVA 230V / 8kVA 240V
Outlet socket (16A)	2
Inlet plug (16A)	1
Avg. sound pressure	63 dB(A) @ 7m
Tank capacity (gross/net)	200/180 l
Running time	140 h
Liquid containment (110%)	√
Wind speed resistance	110 km/h



Picture shown may not reflect actual configuration.