



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 2010200

Air operated pump s. C20F for grease with 20 kg reservoir (internal \varnothing 255÷300 mm), R 50:1 and overpressure reversing valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

| | |
|-----------------------------|------------------------------|
| Flow rate | 1330 cm ³ /min |
| Tank capacity | 20 kg |
| Pressure ratio | 50:1 |
| Air inlet connection | G 1/4" (f) |
| Lubricant outlet connection | G 1/4" (f) |
| Working temperature | -25 ÷ +60 °C |
| Lubricant | grease max NLGI 2 |
| Drum internal \varnothing | 255 ÷ 300 mm |
| Pump(R 50:1) | p/n 62648 |
| Drum cover | p/n 10/507 |
| Membrane | p/n 10/63 |
| Packing | No. 2 - 0,094 m ³ |
| Net weight | 13,5 kg |
| Gross weight | 14,1 kg |



OVERALL DIMENSIONS (mm)

