



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 1500200

Air operated pump s. C15F for grease with 20 kg reservoir (internal $\varnothing$ 255÷300 mm), R 50:1 and air operated discharging valve

AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Centralized lubrication, Shipping and offshore, Railway transport

FEATURES

Flow rate	1330 cm ³ /min
Tank capacity	20 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 3/8" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	grease max NLGI 2
Drum internal $\varnothing$	255 ÷ 300 mm
Pump(R 50:1)	p/n 62548
Drum cover	p/n 10/507
Membrane	p/n 10/63
Packing	No. 2 - 0,089 m ³
Net weight	13,2 kg
Gross weight	13,9 kg



OVERALL DIMENSIONS (mm)

