



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 33/2611NHHV2

Diaphragm pump in aluminum series AB-1 with membranes in NBR, balls and seats in Hytrel®

AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

FEATURES

Flow rate	170 l/min
Ratio	1:1
Compatible fluids	water, mineral-vegetable oils, diesel fuel
Pump material	aluminum
Ball valve material	Hytrel®
Air inlet connection	G 3/8" (f)
Fluid inlet-outlet connection	G 1.1/4" (f) x G 1" (f)
Air working pressure	2 ÷ 6 bar
Max supply pressure	8 bar
Average air consumption	1200 l/min
Noise level	75 dB
Fluid temperature	-10 ÷ +90 °C
Max solids diameter	ø 3 mm
Suitable for drums or tanks	-
Suction-delivery ball valve with spring	ball valve with spring



Packing	No. 1 - 0,025 m3
---------	------------------

Weight	14 kg
--------	-------